





COMPANY PROFILE

企业简介

广州鸿添电子科技有限公司成立于2017年。注册资金300万。是一家集舞台特效设备研究、设计、生产、销售、及售后服务于一体的专业厂家；利用最先进技术专业生产舞台喷花机、LED速喷气柱机、薄雾机、烟机、雪花机、泡泡机、彩纸机、二氧化碳气柱及舞台烟雾油等系列舞台特效设备产品，其产品已广泛应用于舞台舞厅、电视台、歌剧院、KTV、酒吧、及影视娱乐城等场所。公司始终秉承“以服务为基础，以质量求生存，以科技创新求发展”的企业宗旨。在舞台设备行业不断开拓及创新。随着技术团队不断成熟与完善，致力于舞台整体特效的解决方案。半年内以其极具性价比的产品，在全国各地的门市店发展为20多家，并积极为国内外客户提供优质的OEM,ODM服务，受到业内的一致好评，为舞台特效行业带来了一番新的气象。同时以“以人才和技术为基础，创造最佳产品和服务”为服务理念，依托高素质的研发团队，强大的技术优势，同时生产各环节严格依照ISO9001品质管理与品质保证系统的要求，坚持采用优质进口原材料和配件并不断提高加工工艺水平，使得质量，性能精益求精。为客户提供极具市场竞争力的产品。真正实现的企业与客户之间的“双赢”。

Guangzhou Hontim Electronic Technology Co.,Ltd was founded in 2017 with 3 million registered capital. Hontim is a professional stage equipment manufacturer that provides research, design, manufacture, sale and after-sale service. We used most advanced technology to produce a wide range of stage effect equipment, such as Sparkler machine, LED Jet Fog Machine, Fazer machine, Hazer Machine, Smoke Machine, Snow Machine, Bubble machine, Confetti machine, LED Co2 Gas Column Machine and stage smoke fog oil. etc. These products are widely used in Stage, Ballroom, TV station, Opera House, KTV, Pub and other places of entertainment. Hontim adhering to the "Service-based, Survive on Quality, Scientific and Technological Innovation-based for development" is the enterprise tenet. It constantly develops and innovates in the stage equipment industry. With the continuous maturity and improvement of the technical team, we are committed to the solution of the overall special effects of the stage. Within half a year, with its cost-effective products, we have developed more than 20 stores in various parts of the country, and actively provide quality products for domestic and foreign customers OEM, ODM service, praised by the industry, brought a new atmosphere for the stage special effects industry. At the same time, with the concept of "creating the best products and services based on talents and technology", relying on high-quality R&D team, strong technical advantages, and at the same time, all aspects of production are strictly in accordance with the requirements of ISO9001 quality management and quality assurance system. The use of high-quality imported raw materials and accessories and continuous improvement of the level of processing technology, resulting in quality and performance excellence. What HONTIM do is to provide customers with highly competitive products and really achieve the "win-win" between Hontim and customers.




西班牙音乐节现场



荷兰party现场



江苏芳甸音乐节现场



郑州心悦年会现场



法国婚礼现场




迪拜婚礼现场



水雾机婚礼现场案例




2019中国好声音广西赛区总决赛



青岛菲菲酒吧现场



MIAMI酒吧现场



KING酒吧现场



奥斯卡酒吧现场

CONTENTS

目录

烟油耗材系列
P16-P21

酒吧氛围系列
P12-P15

辅助特效系列
P09-P11

直喷烟机系列
P07-P08

水性薄雾系列
P06

油性薄雾系列
P05

明星产品系列
P01-P04

舞美粉
雾化油
水性雾油
水性烟油
雪花油
泡泡油
气柱烟油
喷火油
烟饼
彩纸

喷火机
LED 二氧化碳气柱机
二氧化碳气柱枪
LED 二氧化碳彩纸机
彩炮枪

雪花机
迷你干冰机
摇头泡沫机
电动彩纸机
龙卷风彩纸机
特效风扇

DMX直喷烟机
直喷烟机


水性薄雾机

油性双雾机

双喷花机/倒挂喷花
单喷花机
速喷立停LED气柱机
水雾低烟机

烟花机

Spark Fog Machine




MISS-K 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 2400W	Rated Power:2400W
限流保险: 15A/25A	Fuse:15A or 25A
烟雾/喷花部分预热时间:<6mins	Smoke/Spark warming up time: <6mins
烟量输出:10000Cu ft/min	Smoke output:10000Cu ft/min
烟柱高度:7M	Smoke heigh: 7M
火花高度: 室内3M/室外5M	Spark shoot heigh: Indoor 3m/outdoor 5m
灯光参数: 6颗3W添鑫RGBA4合1 LED	LED Specification: RGBA 4 in 1 LED 8W*6Pcs
控制模式: DMX512/无线遥控/ID卡/手动	Control Mode: DMX512/Wireless controller/ ID card / Manual
通 道: 9CH	DMX Channel:9CH
"烟花/烟雾大小: 1%—100%线性调节 (控台)"	Spark & Fog Output:1%-100% Linear adjustment (DMX console)
操控界面: LCD全彩显示	Control Board: LCD display board
油桶容量: 2升	Liquid capacity:2 Liters
配套耗材: 特制金属粉和气柱油	Supporting Supplies:Special Metal Powder & Air column oil
电子温度保护: 支持	Electronic Temperature Protection: Support
无油保护: 支持	Oil Free Protection: Support
毛重: 8.2KG	Gross Weight:19KG
包装尺寸: 490*360*415 MM	Packaging Volume(mm):490*360*415

倒挂喷花机


Hang-up Spark Machine



DR-K 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 790W	Rated Power:790W
限流保险: 4A/8A	Fuse:4A or 8A
预热时间: <8分钟	Spark Initial Warm up Time:<8 mins
喷射高度: 2-7M	Spark Height :2-7M
控制模式: DMX512/无线遥控/ID卡/手动	Control Mode: DMX512/Wireless controller/ ID card / Manual
通道: 2CH	DMX Channel:2CH
"烟花大小: 1%—100%线性调节 (控台)"	Spark Output:1%-100% Linear adjustment (DMX console)
显示屏: 液晶显示板	Control Board: LCD display board
电子温度保护: 支持	Electronic Temperature Protection: Support
配套耗材: 特制金属粉(舞美粉200g/包)	Supporting Supplies:Special Metal Powder (Composite Ti 200g/Pack)
毛重: 8.2KG	Gross Weight:8.2KG
包装尺寸: 275*275*290 MM	Packaging Volume(mm):275*275*290

喷花机
Spark Machine



MINI-K4 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：500W	Rated Power:500W
限流保险：4A/8A	Fuse:4A or 8A
预热时间：<8分钟	Spark Initial Warm up Time:<8 mins
喷射高度：1-4M	Spark Height :1-4M
控制模式：DMX512/无线遥控/ID卡/手动	Control Mode: DMX512/Wireless controller/ ID card / Manual
通道：2CH	DMX Channel:2CH
"烟花大小：1%—100%线性调节（控台）"	Spark Output:1%-100% Linear adjustment (DMX console)
显示屏：液晶显示板	Control Board: LCD display board
电子温度保护：支持	Electronic Temperature Protection: Support
配套耗材：特制金属粉(舞美粉200g/包)	Supporting Supplies:Special Metal Powder （Composite Ti 200g/Pack）
毛重：7.5KG	Gross Weight:7.5KG
包装尺寸：260*260*310 MM	Packaging Volume(mm):260*260*310



NS-3 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：420W	Rated Power:420W
限流保险：4A/8A	Fuse:4A or 8A
预热时间：<6分钟	Spark Initial Warm up Time:<6 mins
喷射高度：1-3M	Spark Height :1-3M
"控制模式：DMX512/无线遥控"	Control Mode:DMX512/Wireless
通道：2CH	DMX Channel:2CH
"烟花大小：1%—100%线性调节（控台）"	Spark Output:1%-100% Linear adjustment (DMX console)
显示屏：数字显示板	Display Board: Digital display board
电子温度保护：支持	Electronic Temperature Protection: Support
配套耗材：特制金属粉(舞美粉200g/包)	Supporting Supplies:Special Metal Powder （Composite Ti 200g/Pack）
毛重：7.8KG	Gross Weight:7.8KG
包装尺寸：300*300*320MM	Packaging Volume(mm):300*300*320

速喷立停LED气柱机
Speed Spray Vertical Stop Led
Gas Column Machine



ML-30 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：3000W	Rated Power: 3000W
预热时间:<8 mins	Pre-heating Time:<8minutes
灯光参数：36颗*1W红绿蓝三合一LED	LED Specification: 36Pcs*1W RGB 3in1 LED
控制模式：DMX512/无线遥控/手动	Control Mode: DMX512/Wireless controller/ Manual
喷烟高度：>13-15米	Fog Height:>13-15M
烟量输出:28000Cu ft/min	Smoke Output:28000 Cu ft/ min
通 道：11CH	DMX Channel:11CH
喷烟角度：直喷/上喷/倒挂	Fog Shoot Angle:Side+ upside-down+ up-spraying
喷烟特点：速喷立停	Fog Features:Quick jet and immediately stop
操作界面：LCD全液晶触控显示	Control Board: LCD Touch display board
电子温度保护：支持	Electronic Temperature Protection: Support
耗油量：15分钟/L(100%)	Fuel Consumption:15 Minutes/L （100%）
油桶容量：5L	Tank Capacity:5L
毛重：16.5KG	Gross Weight:16.5KG
尺 寸：460*385*260 MM	Packaging Volume(mm):460*385*260

ML-20 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：2000W	Rated Power: 2000W
预热时间:<6 mins	Pre-heating Time:<6 minutes
灯光参数：36颗*1W红绿蓝三合一LED	LED Specification: 36Pcs*1W RGB 3in1 LED
控制模式：DMX512/无线遥控/手动	Control Mode: DMX512/Wireless controller/ Manual
喷烟高度：>8-10米	Fog Height:>8-10M
烟量输出:25000Cu ft/min	Smoke Output:25000 Cu ft/ min
通 道：11CH	DMX Channel:11CH
喷烟角度：直喷/上喷/倒挂	Fog Shoot Angle:Side+ upside-down+ up-spraying
喷烟特点：速喷立停	Fog Features:Quick jet and immediately stop
操作界面：LCD全液晶触控显示	Control Board: LCD Touch display board
电子温度保护：支持	Electronic Temperature Protection: Support
耗油量：20分钟/L(100%)	Fuel Consumption:20 Minutes/L （100%）
油桶容量：5L	Tank Capacity:5L
毛重：16KG	Gross Weight: 16KG
尺 寸：460*385*260 MM	Packaging Volume(mm):460*385*260



水雾低烟机
Water Mist Machine



MLF-3000 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 2100W	Rated Power: 2100W
预热时间:<4 mins	Pre-heating Time:<4 minutes
电子温度保护: 支持	Electronic Temperature Protection: Support
无油保护: 支持	Oil Free Protection: Support
控制模式: DMX512/无线遥控/手动	Control Mode: DMX512/Wireless controller/ Manual
通 道: 2CH	DMX Channel: 2CH
油桶容量: 1.5L	Tank Capacity: 1.5L
水雾化量:30000mL/h	The Amount Of Water Mist:30000mL/h
烟量输出:20000Cu ft/min	Smoke Output:20000 Cu ft/min
喷烟距离: >7-10米	Fog Distance:>7-10M
喷管长度: 3米+铁喷头	Nozzle Pipe length:3 M + Nozzle
操作界面: LCD中英文触控显示	Control Board:LCD Chinese and English display Board
包装: 航空箱	Packing:Flight case
机器尺寸:740*380*530mm	Machine Size:740*380*530mm
毛重:45KG	Gross Weight: 45KG
包装尺寸:785*400*540mm	Packaging Volume(mm):785*400*540mm

MLF-4000 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 3000W	Rated Power: 3000W
预热时间:<4 mins	Pre-heating Time:<4 minutes
电子温度保护: 支持	Electronic Temperature Protection: Support
无油保护: 支持	Oil Free Protection: Support
控制模式: DMX512/无线遥控/手动	Control Mode: DMX512/Wireless controller/ Manual
通 道: 2CH	DMX Channel: 2CH
烟量输出:20000Cu ft/min	Smoke Output:20000 Cu ft/min
油桶容量: 3L	Tank Capacity: 3L
耗油 量: 120分钟/L(30%) 45分钟/L(100%)	Fuel Consumption:120 Minutes/L (30%) 45Minutes/L (100%)
喷烟距离: >7-10米	Fog Distance:>7-10M
喷管长度: 3米+铁喷头	Nozzle Pipe length:3 M + Nozzle
操作界面: LCD 数码触控显示	Control Board:LCD Digital touch display
包装: 航空箱	Packing:Flight case
重量: 51KG	Gross Weight: 51KG
尺寸: 870*735*630MM	Packaging Volume(mm):870*735*630MM

油性双雾机
Double Hazer Machine



HZ-750 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 800W	Rated Power: 800W
预热时间: 不需要	Pre-heating Time:No need
电子温度保护: 支持	Electronic Temperature Protection: Support
耗油量:1200mins/L(100%)	Oil consumption:1200mins/L(100%)
烟量输出:3000Cu ft/min	Smoke Output: 3000Cu ft/min
油桶容量:3.2L	Capacity of oil tank:3.2L
风扇角度: 30-90度机械可调	Fan angle adjustment:Support(30-90 degree mechanically adjustable)
风力大小: 1—10档调节	Fan Speed Adjustment:Support(1-10 adjustment)
操作界面: LCD中英文触控显示	Display Board:LCD Chinese and English display
控制模式: DMX512/无线遥控/手动	Control Mode:DMX512/Wireless controller/Manual
通道: 2CH	DMX Channel: 2CH
包装: 航空箱	Packing:Flight case
配套耗材: HZL系列油性雾油	Supporting Supplies:HZL-III High Purity Hazer liquid
重量: 34.7KG	Gross weight:34.7KG
尺寸: 590*450*480(mm)	Packaging(mm): 590*450*480(mm)

H-5 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 600W	Rated Power: 600W
预热时间: 不需要	Pre-heating Time:No need
电子温度保护: 支持	Electronic Temperature Protection: Support
耗油量:1080mins/L(100%)	Oil consumption:1080mins/L(100%)
烟量输出:3000Cu ft/min	Smoke Output: 3000Cu ft/min
油桶容量:3.2L	Capacity of oil tank:3.2L
风扇角度: 30-90度机械可调	Fan angle adjustment:Support(30-90 degree mechanically adjustable)
风力大小: 1—10档调节	Fan Speed Adjustment:Support(1-10 adjustment)
操作界面: 数码触控显示	Display Board:Digital display
控制模式: DMX512/无线遥控/手动	Control Mode:DMX512/Wireless controller/Manual
通道: 2CH	DMX Channel: 2CH
包装: 航空箱	Packing:Flight case
配套耗材: HZL系列油性雾油	Supporting Supplies:HZL-III High Purity Hazer liquid
重量: 27.54KG	Gross weight:27.54KG
尺寸: 520*396*413mm	Packaging(mm): 520*396*413mm



水性薄雾机 Fazer Machine



F-6 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 1500W	Rated Power: 1500W
预热时间: <2分钟	Pre-heating Time:<2 minutes
耗 油 量: 160分钟/L(30%) 50分钟/L(100%)	Fuel Consumption:160 Minutes/L (30%) 50Minutes/L (100%)
烟量输出:4600Cu ft/min	Smoke Output:4600 Cu ft/ min
控制模式: DMX512/手动/定时定量	Control Mode: DMX512/ Manual/Timer
通 道: 2CH	DMX Channel: 2CH
油桶容量: 5L	Tank Capacity: 5L
风扇角度: 0-60度机械可调	Fan Angle:0-60 degree mechanical adjustable
风力大小: 1%—100%线性调节	Fan Speed :1%-100% Linear adjustment
烟量大小: 1%—100%线性调节	Fog Output:1%-100% Linear adjustment
操作界面: LCD触控显示	Control Board:LCD Touch Display board
电子温度保护: 支持	Electronic Temperature Protection: Support
定时控制: 支持	Time Control:Support
无油保护: 支持	Oil-Free protection: Support
重 量: 15KG	Weight:15KG
尺 寸: 590*330*450MM	Size:590*330*450MM

FZ-1700 参数 SPECIFICATION

使用电压:AC220-230V/50HZ 或 AC110-120V/60HZ	Voltage Used AC220-230V/50HZ or AC110-120V/60HZ
功率:1200W	Power:1200W
保险:6.3A(220V)/12A(110V)	Fuse:6.3A(220V)/12A(110V)
预热时间:2Min	Pre-heating Time:2Min
电子恒温控制:支持	Electronic Temperature Control:Support
耗油量:900ml/h(100%)	Oil Comsumption:900ml/h(100%)
烟量输出:4500Cu ft/min	Smoke Output:4500Cu ft/min
油桶容量:2L	Capacity Of Oil Tank:2L
烟量/风力大小: 1%—100%线性调节	Fog/Fan Speed :1%-100% Linear adjustment
显示屏: LCD display	Display Board: LCD Display
控制模式: DMX512/手动/无线遥控	Control Mode: DMX512/ Manual/Wireless Remote
DMX通道: 2CH	DMX Channel: 2CH
无油保护: 支持	Low Fog Fluid Shut Off Sensor Function: Support
毛重: 17KG	Gross Weight: 17KG
包装尺寸: 620*380*370mm	Packaging: 620*380*370mm



DMX直喷烟机 Double Hazer Machine



VJ-3000 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 3000W	Rated Power: 3000W
限流保险: 10A/15A	Fuse:10A or 15A
预热时间: <10分钟	Pre-heating Time:<10 minutes
耗 油 量: 8分钟/L(100%)	Fuel Consumption: 8 Minutes/L (100%)
烟量输出:30400 Cu ft/ min	Fog Volume: 30400 Cu ft/ min
控制模式: DMX512/遥控/定时定量控制	Control Mode: DMX512/ Manual/Timer
通 道: 1CH	DMX Channel: 1CH
操作界面: 数码触控显示	Control Board:Digital display board
油桶容量: 3L	Tank Capacity: 3L
烟量大小: 机械线性调节	Fog Output:Mechanical linear regulation
电子温度保护: 支持	Electronic Temperature Protection: Support
定时定量控制: 支持	Time Control:Support
配套耗材: FL/HL系列水性烟雾油	Supporting Supplies:FL/HL Series Water-based Smoke Oils
重 量: 6.7KG	Weight:6.7 KG
尺 寸: 450*255*280MM	Size: 450*255*280MM

VJ-1500 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 1500W	Rated Power: 1500W
限流保险: 8A/15A	Fuse:8A or 15A
预热时间: <6分钟	Pre-heating Time:<6 minutes
耗 油 量: 10分钟/L(100%)	Fuel Consumption: 10 Minutes/L (100%)
烟量输出:20000 Cu ft/ min	Fog Volume: 20000 Cu ft/ min
控制模式: DMX512/遥控/定时定量控制	Control Mode: DMX512/ Manual/Timer
通 道: 1CH	DMX Channel: 1CH
操作界面: 数码触控显示	Control Board:Digital display board
油桶容量: 2.5L	Tank Capacity: 2.5L
烟量大小: 机械线性调节	Fog Output:Mechanical linear regulation
电子温度保护: 支持	Electronic Temperature Protection: Support
定时定量控制: 支持	Time Control:Support
配套耗材: FL/HL系列水性烟雾油	Supporting Supplies:FL/HL Series Water-based Smoke Oils
重 量: 4.2KG	Weight: 4.2KG
尺 寸: 370*205*250MM	Size: 370*205*250MM



直喷烟机
Fog Machine



N-1500C/900C 参数 SPECIFICATION

额定电压Voltage Used:	AC220V /50Hz or AC120V/60Hz	AC220V /50Hz or AC120V/60Hz
功率Rated Power:	1500W	900W
限流保险Fuse:	8A or 15A	5A or 10A
预热时间Pre-heating Time:	<6 minutes	<3 minutes
烟量输出Fog Volume:	20000 Cu ft/ min	10000 Cu ft/ min
控制模式Control Mode:	Wireless Controller/Wired Controller 遥控/线控	Wireless Controller/Wired Controller 遥控/线控
油桶容量Tank Capacity:	2.3L	0.4L
电子温度保护Electronic Temperature Protection:	Support支持	Support支持
配套耗材Supporting Supplies:	FL/HL Series Water-based Smoke Oils	FL/HL Series Water-based Smoke Oils
毛重Gross Weight:	4.74KG	1.96 KG
尺寸Packaging Volume(mm):	382*295*189MM	242*195*132mm



N-400A 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：400W	Rated Power: 400W
预热时间：<2分钟	Pre-heating Time:<2 minutes
烟量输出:3000 Cu ft/ min	Fog Volume: 3000 Cu ft/ min
控制模式： 遥控/线控	Control Mode: Wireless Controller/Wired Controller
油桶容量： 0.25 L	Tank Capacity: 0.25L
机械温度控制： 支持	Mechanical Temperature Control: Support
配套耗材： FL/HL系列水性烟雾油	Supporting Supplies: FL/HL Series Water-based Smoke Oils
毛重： 1.94 KG	Gross Weight: 1.94 KG
尺 寸： 250*195*200mm	Packaging Volume(mm):250*195*200mm



大雪花机
Snow Machine



迷你干冰机
Mini Dry Ice Machine



MS-1250T 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：1400W	Rated Power: 1400W
限流保险：5A/10A	Fuse:5A or 10A
预热时间：无需	Pre-heating Time:No need
耗油 量：20分钟/L(30%) 10分钟/L(100%)	Fuel Consumption:20 Minutes/L (30%) 10Minutes/L (100%)
雪花量输出:3000 Cu ft/ min	Snowflake output: 3000 Cu ft/ min
控制模式：DMX512/遥控/定时定量控制	Control Mode: DMX512/ Manual/Timer
通 道：1CH	DMX Channel: 1CH
雪花喷射距离：7M	Snowflake jet distance: 7M
风力大小：1%－100%线性调节	Fan speed:1%-100% linear adjustment
雪花粒大小：2档	Snowflake size: 2 files
操作界面：数码触控显示	Digital display board
定量控制：支持	Time Control:Support
无油保护：支持	Low Fog Fluid Shut Off Sensor Function Support
配套耗材：SL雪花油系列	Supporting Supplies: SL High Volatile Snowflake juice
毛重:9.42KG	Gross weight:9.42KG
包装尺寸:575*350*320(mm)	Packaging Volume(mm): 575*350*320(mm)

Z-6/Z-3 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率： (Z-6)6000W/(Z-3)3000W	Rated Power: (Z-6)6000W/(Z-3)3000W
预热时间：<15 Minutes	Pre-heating Time:< 15Minutes
耗油 量：3-5分钟/L(100%)	Fuel Consumption: 3-5Minutes/L (100%)
覆盖面积：7100 Cu ft/ min	Coverage arean:7100 Cu ft/ min
喷烟距离：>7-10米	Jet Distance:>7-10M
控制模式：DMX512/手动	Control Mode: DMX512/Manual
通 道：1CH	DMX Channel: 1CH
油桶容量：8L（水）+3.5L（干冰）	Tank Capacity: 8L (Water) +3.5L (Dry ice)
喷管长度：3米+铁喷嘴	Nozzle Pipe length: 3 M + Nozzle
配套耗材：干冰	Supporting Supplies:Dry ice
重量：(Z-6)10.5KG /(Z-3)8KG	Weight: (Z-6)10.5KG /(Z-3)8KG
尺 寸：490*450*465mm(Z-6)	Size:490*450*465mm(Z-6)
415*345*340mm(Z-3)	415*345*340mm(Z-3)


摇头泡沫机 Big Foam Machine



SF-8000 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 1800W	Rated Power: 1800W
耗油 量: 1 Minute/L (100%)	Fuel Consumption: 1 Minute/L (100%)
控制模式: DMX512/无线远程遥控/手动	DMX512/Wireless contrller/Manual
通道: 2CH	DMX Channel: 2CH
喷射距离: >8-10米	Jet Distance:>8-10M
烟量输出: 120平方米/分钟	Smoke output: 120 square meters / minute
油桶容量: 40L	Tank Capacity: 40L
泡沫喷射量 60m³/h	The amount of foam jetting:60m³/h
左右摇头角度 80°	Left/ Right Shaking Angle 80°
上下摇头角度 53°	Up/downj shaking angle 53°
操作界面: 数码触控显示	Controler Board: Digital display board
配套耗材: 泡沫水/泡沫粉	Supporting Supplies: Foam water / Foam powder
重 量: 73.88KG	Gross Weight 73.88KG
尺 寸: 1140*640*1510MM	Packaging 1140*640*1510mm

电动彩纸机 Confetti Machine



MCF-2000 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 1250W	Rated Power: 1250W
灯光参数: 6颗*8W RGBW四合一LED	LED specification: RGBA 4IN1 *8W*6PCS
喷射高度: 3—5米	Jet Height:3-5M
控制模式: DMX512/无线遥控/线控	Control Mode:DMX512/Wireless controller/Wired controller
通道: 5CH	DMX Channel: 5CH
储纸容量: 2KG	Paper storage capacity:2KG
喷射角度: 0-180度机械可调	Injection angle: 0-180 degrees mechanically adjustable
操作界面: 数码触控显示	Control Board: Digital board
配套耗材: PG彩纸系列	Supporting Supplies: PG Colored paper series
重 量: 11.86KG	Gross weight: 11.86kg
尺 寸: 360*350*550MM	Packaging(mm): 360*350*550 (mm)

龙卷风彩纸机 Tornado Confetti Machine



CP-2000 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 400W	Rated Power: 400W
耗气 量: 1-2次/L	Air consumption:1-2 Times/L
存 纸 量: 10KG(满载)	Paper Tank Capacity:10KG (Full filled)
喷射高度: >10米	Jet Height: >10M
最大压力: 8bar	Maximum Pressure:8bar
控制模式: DMX512/手动	Control Mode:DMX512/Manual
通道: 1CH	DMX Channel:1CH
连接管道: 3米+3米 (标配)	Connect Pipe:3m+3m(Standard)
喷射角度: 0-160度机械可调	Jet Angle:0-160 degree mechanical adjustable
操作界面: 数码触控显示	Controler Board:Digital display board
配套耗材: 彩纸+Co2	Consumables: Confetti + Co2
重 量: 16.9KG	Net Weight:16.9KG
尺 寸: 600*600*465mm	Machine Volume: 600*600*465mm

特效风扇 DMX special effect fan



MF-1 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 200W	Rated Power: 200W
限流保险: 2A/4A	Fuse:2A or 4A
风量输出: 3300立方米/小时	Fan Volume Output:117000 Cu ft/ Hour
风力距离: 烟雾推送距离>20米 (100%)	Fan Speed distanace:Smoke Push Distance > 20 m (100%)
控制模式: DMX512/无线远程遥控/手动/定时定量	Control Mode: DMX512/Wireless controller/ Manual /Timer
通道: 1CH	DMX Channel: 1CH
风扇角度: 0-180度机械可调	Fan Angle:0-180 degree mechanical adjustable
风力大小: 1%—100%线性调节	Fan Speed Adjustment:1%-100% Linear adjustment
操作界面: LCD中英文触控显示	Control Board:LCD Chinese and English Display board
定时定量控制: 支持	Timer control:Suppprt
音量: 66bdb(A)	Noise: 66bdb(A)
重 量: 12KG	Gross Weight: 12KG
尺 寸: 470*310*520MM	Packaging Volume(mm):470*310*520MM

三管喷火机
Flame Machine



SF-180 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 500W	Rated Power:500W
预热时间: 无需预热	Initial Warming up time:NO NEED
耗 油 量: 8-10次/500ML/瓶(持续1-3秒)	Fuel Consumption:8-10 Times/500ML/Bottle (Last 1-3 seconds)
喷射高度: >1-3米	Jet Height:>1-3M
最大压力: 6bar	Maximum Pressure:6bar
控制模式: DMX512/手动	Control Mode: DMX512/Manual
操作界面: 拔码开关/启动开关	Controler Board:Dip Switch/Start Switch
配套耗材: 500ML/瓶 喷火油	Supporting Supplies:500ML/Bottle Flame oil
重 量: 7.5KG	Weight:7.5KG
尺 寸: 290*300*230MM	Size:290*300*230MM

单管喷火机
Flame Machine



SF-181 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 200W	Rated Power:200W
预热时间: 无需预热	Initial Warming up time:NO NEED
耗 油 量: 8-10次/500ML/瓶(持续1-3秒)	Fuel Consumption:8-10 Times/500ML/Bottle (Last 1-3 seconds)
喷射高度: >1-3米	Jet Height:>1-3M
最大压力: 6bar	Maximum Pressure:6bar
控制模式: DMX512/手动	Control Mode: DMX512/Manual
操作界面: 拔码开关/启动开关	Controler Board:Dip Switch/Start Switch
配套耗材: 500ML/瓶 喷火油	Supporting Supplies:500ML/Bottle Flame oil
重 量: 6.5KG	Weight:6.5KG
尺 寸: 300*230*230MM	Size:300*230*230MM

LED二氧化碳气柱机
LED Co2 Machine



MC-300C 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率: 60W	Rated Power: 60W
灯光参数: 12颗*3W添鑫 RGB三合一LED	LED Specification:12pcs*3W*LED 3in 1 RGB
耗 气 量: 3—4次/L(持续3秒)	Air Consumption:3-4times/L (Last 3 seconds)
喷射高度: >8米	Jet Height:>8M
最大压力: 8bar	Maximum Pressure: 8bar
控制模式: DMX512/无线远程遥控/手动	Control Mode: DMX512/Wireless controller/Manual
通道: 7CH	DMX Channel: 7CH
连接管道: 3米	Connect Pipe: 3M
喷射角度: 0-180度机械可调	Jet angle: 0-180 degree mechanical adjustable
操作界面: 数码触控显示	Controler Board: Digital display board
配套耗材: 20L/40L CO2	Supporting Supplies: 20L/40L CO2
重 量: 7.3KG	Weight:7.3KG
尺 寸: 435*355*235MM	Size:435*355*235MM




二氧化碳气柱枪
Co2 Gun



MC-150C 参数 SPECIFICATION

额定电压: AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功率: 30W	Rated Power: 30W
LED参数: 4*3W颜色可选	LED Specification:4*3W color optional
电池参数: 5号电池 4节	Battery Specification: No.5 Battery *4pcs
耗 气 量: 3—5次/L(持续3秒)	Air Consumption: 3-5times/L (Last 3 seconds)
烟量输出: 130立方米/分钟	Fog Volume:4600 Cu ft/ min
喷射高度: >6-7米	Jet Height:>6-7m
最大压力: 8bar	Maximum Pressure: 8bar
控制模式: 手动	Control Mode:Manual
连接管道: 3米	Connect Pipe: 3M
喷射角度: 手持随意角度	Jet angle: Random angle(Hand-held)
配套配件: 5L带气气瓶、背带、气管	Parts: 5 L Air Cylinders、Belts、Connector
配套耗材: 5L CO2	Supporting Supplies: 5L Co2
重 量: 20KG	Weight:20KG
尺 寸: 780*247*80MM	Size: 780*247*80MM



LED二氧化碳气柱枪
LED Co2 Gun



MC-150 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
耗 气 量：3—5次/L(持续3秒)	Air Consumption: 3-5times/L （Last 3 seconds）
烟量输出：130立方米/分钟	Fog Volume:4600 Cu ft/ min
喷射高度：>6米	Jet Height:>6m
最大压力：6bar	Maximum Pressure: 6bar
控制模式：手动	Control Mode:Manual
连接管道：3米	Connect Pipe: 3M
喷射角度：手持随意角度	Jet angle: Random angle(Hand-held)
配套配件：5L带气气瓶、背带、气管	Parts: 5 L Air Cylinders、Belts、Connector
配套耗材：5L Co2	Supporting Supplies: 5L Co2
重 量：20KG	Weight:20KG
尺 寸：680*280*160MM	Size: 680*280*160MM


LED二氧化碳彩纸机
LED Co2 Confetti Machine



MCP-600 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：200W	Rated Power: 200W
灯光参数：12颗*3W RGB三合一LED灯珠	LED Specification:12pcs*3WRGB*3in1 LED
耗 气 量：3-4次/L	Air Consumption:3-4times/L
存 纸 量：4KG（满载）	Paper Tank Capacity:4KG （full filled）
喷射高度：>8米	Jet Height:>8m
最大压力：8bar	Maximum Pressure:8bar
控制模式：DMX512/手动	Control Mode: DMX512/Manual
通 道：1CH	DMX Channel:1CH
连接管道：3米（标配）	Connect Pipe:3m （Standard）
喷射角度：30-160度机械可调	Jet angle:30-160degree mechanical adjustable
操作界面：数码触控显示	Controler Board: Digital display board
配套耗材：20L/40L CO2+PG彩纸系列	Supporting Supplies:20L/40L Co2 PG Series Confetti paper
重 量：9KG	Weight:9KG
尺 寸：550*200*200MM	Size:550*200*200MM

彩炮枪
Confetti Gun



MCP-3 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：100W	Rated Power: 100W
耗 油 量：1根/次	Fuel Consumption:1pc/time
纸量输出：10-20平方米/次	Confetti Output:360-710 Cu ft/time
喷射高度：>8米	Jet Height:>8M
最大压力：<6bar	Maximum Pressure:<6bar
控制模式：手动	Control Mode:Manual
喷射次数：三管三次	Numbers of Jet:3 Times for 3 tubes
喷射角度：手持随意角度	Jet angle:Random angle(Hand-held)
配套耗材：电子礼炮	Supporting Supplies:Electronic salute
重 量：2.KG	Weight:2KG
尺 寸：555*140*240MM	Size:555*140*240MM

加特林彩炮枪
Gatlin Confetti Gun



MCP-6 参数 SPECIFICATION

额定电压：AC220V /50Hz 或 AC120V/60Hz	Voltage Used:AC220V /50Hz or AC120V/60Hz
功 率：300W	Rated Power: 300W
耗 油 量：1根/次	Fuel Consumption:1pc/time
LED灯光参数：200颗小功率炫彩灯珠+6颗*3W蓝色LED灯	LED Specification:200pcs colorful LED+6pcs*3W blue LED
纸量输出：10-20平方米/次	Confetti Output:360-710 Cu ft/time
喷射高度：>8米	Jet Height:>8M
最大压力：<6bar	Maximum Pressure:<6bar
控制模式：手动	Control Mode:Manual
喷射次数：6管6次	Numbers of Jet:6 Times for 6 tubes
喷射角度：手持随意角度	Jet angle:Random angle(Hand-held)
配套耗材：电子礼炮	Supporting Supplies:Electronic salute
重 量：15KG	Weight:15KG
尺 寸：950*230*280MM	Size:950*230*280MM

烟油耗材系列

Smoke oil consumables series



舞美粉
Composite Ti

本品为室内舞美粉，仅适用我厂生产的喷花机。每包独立真空包装，配卡使用。
容量：1包=200g
This product is our FX indoor powder. It is only suitable for the spark machine that produced by our factory. Each package is packed independently in vacuum and used with cards.
Capacity: 1 package = 200g



HZL-III
三代高纯雾化油
High Purity Hazer liquid

HZL-III：无色、无味、非燃性。III 代油性烟雾油相对第一代油性雾油产生的细雾更具质感，更细腻，更匀称，在空气中保留的时间更长，是专为高级Haze机器所设计的最新型环保特效烟油。宛如黄金的特性，稳定，质纯，产生的烟雾细致，高质感，能与灯光交汇出最完美的艳丽效果。透明的烟雾，非常干燥，具有极强的持久性，不伤害人体健康和影响环境。可以加强Haze机器的效果及延长机器的使用寿命。
容量：1L/瓶 6瓶/箱
HZL-III: Colorless, Tasteless, Non-flammable. The third generation of Hazer liquid is more textural, more delicate and more symmetrical than the first generation of hazer liquid. It is the latest type of special environmental protection hazer liquid that specially designed for advanced Haze machines. Just like the characteristics of gold, stable, pure, the smoke produced is meticulous, high texture, and can intersect with the lights to produce the most perfect gorgeous effect. Transparent smoke, very dry, very durable, does not harm human health and affect the environment. It can enhance the effect of Haze machine and prolong its service life.
Capacity: 1L/Bottle 6 Bottles/carton Colorless High Purity Hazer liquid



VL-5
专业水性薄雾油
Water-based Hazer liquid

VL-5型水性薄雾油采用蒸馏水及可食性环保配方制成，产生的烟雾为纯白色，细腻，匀称。非常环保且在空气中保持时间较长，产生的烟雾在20摄氏度室温时可保持在空气中10-15分钟。由于采用了新配方，所以不会产生油质微粒，对光学玻璃及高档摄影设备无污染，并且大幅降低了雾机的阻塞，适合各种高档场所使用。
容量：5L/瓶 4瓶/箱 菠萝香型（标配） 批量可选配其它香型
VL-5 water-based Hazer liquid is made of distilled water and edible environmentally friendly formula. The smoke produced is pure white, fine and symmetrical. It's environmentally friendly and can be kept in the air for a long time, the fog can remain in the air for 3-6 minutes at room temperature of 20 °C. Due to the new formula, it does not produce oily particles, no pollution to optical glass and high-end photographic equipments, and greatly reduces the blockage of the fog machine, So it suitable for use in various high-end places.
Capacity: 5L/bottle 4 bottles / carton, with pineapple flavor (standard), other flavor is optional for mass production



HL-4
重型水性烟油
Heavy-duty water-based fog juice

HL-4重型水性烟油适合大部分厂家的烟雾机，采用蒸馏水及可食性环保配方制成，产生的烟雾为纯白色，非常环保且在空气中保持时间较长，产生的烟雾在20摄氏度室温时可保持在空气中3-6分钟。由于采用了新配方，所以不会产生油质微粒，对光学玻璃及高档摄影设备无污染，并且大幅降低了烟雾机的阻塞，适合各种高档场所使用。
容量：4.5L/瓶 4瓶/箱 菠萝香型（标配） 批量可选配其它香型
HL-4 heavy-duty water-based fog juice is suitable for most manufacturers' smoke machines. It is made of distilled water and edible environmentally friendly formula. The smoke produced is pure white, very environmentally friendly and kept in the air for a long time, the fog can remain in the air for 3-6 minutes at room temperature of 20 °C. Thanks to the new formula, it does not produce oily particles, no pollution to optical glass and high-end photographic equipment, and greatly reduces the clogging of the fog machine, suitable for use in various high-end places.
Capacity: 4.5L/bottle 4 bottles / carton, with pineapple flavor (standard), other flavor is optional for mass production



FL-4 轻型水性烟油 Light water-based fog juice

FL-4轻型水性烟油适合大部分厂家的烟雾机，采用蒸馏水及可食性环保配方制成，产生的烟雾为纯白色，非常环保且在空气中保持时间较长，产生的烟雾在20摄氏度室温时可保持在空气中2-4分钟。由于采用了新配方，所以不会产生油质微粒，对光学玻璃及高档摄影设备无污染，并且大幅降低了烟雾机的阻塞，适合各种高档场所使用。

容量：4.5L/瓶 4瓶/箱 菠萝香型（标配） 批量可选配其它香型

FL-4 light water-based fog juice is suitable for most manufacturers' smoke machines. It is made of distilled water and edible environmentally friendly formula. The smoke produced is pure white, very environmentally friendly and kept in the air for a long time. the fog can remain in the air for 2-4 minutes at room temperature of 20 °C. Thanks to the new formula, it does not produce oily particles, no pollution to optical glass and high-end photographic equipment, and greatly reduces the clogging of the fog machine, suitable for use in various high-end places. Capacity: 4.5L/bottle 4 bottles / carton, with pineapple flavor (standard), other flavor is optional for mass production



SL-5 雪花油 High Volatile Snowflake juice

SL-5高挥发性雪花油，在雪花落下之后很快就会消散，不会造成使用环境的湿滑及残留。同样安全无刺激性成分，同时具备百分百的生物分解性，不污染环境。

容量：5L/瓶 4瓶/箱

Hontim BL-5 new bubble liquid is a kind of water-based synthetic liquid, non-polluting, colorless, odorless, non-flammable, non-irritating and will not cause skin allergies. It can produce a large number of translucent colorful bubbles with high transparency and high refraction. The volume of bubbles is very large, the toughness is not easy to be broken, and the live atmosphere can be activated. It brings you a colorful bubble world, and it can be used in various of bubble machine from different manufacturers.

Capacity: 5L / bottle 4 bottles / carton



BL-5 泡泡油 Bubble liquid

Hontim(鸿添电子) BL-5型新款泡泡油是一种水性合成液，无污染，无色，无味，非燃性，无刺激性及不会造成皮肤过敏搭配鸿添泡泡机系列产品可产生出大量透光性及折射度高的半透明七彩泡泡，泡泡量非常大，韧性好不易破碎，能活跃现场氛围，给您带来五彩缤纷的泡泡世界，通用于各厂家的泡泡机设备！

容量：5L/瓶 4瓶/箱

Hontim BL-5 new bubble liquid is a kind of water-based synthetic liquid, non-polluting, colorless, odorless, non-flammable, non-irritating and will not cause skin allergies. It can produce a large number of translucent colorful bubbles with high transparency and high refraction. The volume of bubbles is very large, the toughness is not easy to be broken, and the live atmosphere can be activated. It brings you a colorful bubble world, and it can be used in various of bubble machine from different manufacturers.

Capacity: 5L / bottle 4 bottles / carton



QL-2 快散型气柱油 Special fast-dissolving air column Fog juice

专用快散型气柱烟油：全新配方，成份完全不同于其它厂家的烟油，全部依托中国环保标准下制成。是专为鸿添电子气柱烟机系列产品研制而成的专用型气柱烟油，产生的烟雾效果浓白纯密，空气中停留时间不会超过10秒。搭配鸿添电子系列气柱机使用，效果可完全媲美二氧化碳气柱机效果

HONTIM special fast-dissolving air column Fog juice: a new formula, the composition is completely different from other manufacturers' fog liquid, all raw material are relying on Chinese environmental protection standards. It is a special type of vertical fog juice that specially developed for our vertical fog machines series. The smoke generated is white and pure, and the air stay time will not exceed 10 seconds. With the use of Hontim series vertical fog machine, the effect can be completely comparable to the CO2 vertical machine effect. capacity: 2L / bottle 8 bottles / carton



SL-2
水雾油
High-purity special Low Fog Juice

HONTIM (鸿添电子) 高纯专用水雾油：全新配方，成份完全不同于其它厂家的烟雾油，全部依托中国环保标准下为鸿添水雾机系列研制而成的专用型水雾低烟油，产生的烟雾效果浓白而又纯密，能长时间沿地翻滚，不上飘，易散，搭配鸿添电子系列水雾机使用，效果可完全媲美干冰效果
容量：2L/瓶 8瓶/箱

HONTIM high-purity special Low Fog Juice: a new formula, the composition is completely different from Fog juice of other manufacturers, All materials are relying on China's environmental protection standards. It is a special type of low fog juice that specially developed for our low fog machines series. The effect of the smoke is thick and pure, and it can roll over the ground for a long time. It is not floating, easy to disperse, If used this low fog juice together with hontim low fog machine. The effect can be completely comparable to the dry ice effect.
Capacity: 2L / bottle 8 bottles / carton



OL-1
喷火油
Flame Liquid

本产品仅适用于舞台喷火机,是一种气雾剂,无毒,非易爆,但有明火的条件泄露会燃烧。
容量：1L/瓶 25瓶/箱


This product is only suitable for stage spray machine. It is a kind of aerosol, non-toxic, non-explosive, but it will burn when there is open fire.
Capacity: 1L/ bottle 25nottles / Carton



YB-2
烟饼
Cigarette Cake

超高密度香型烟饼，烟雾量大，空气中停留时间长，不呛鼻，纯白色，
容量：18片/组 9组/箱

Ultra-high density "cigarette cake", bigger smoke output , long stay in the air, no choking , pure white
capacity: 18 pieces / group ,9 groups /carton



CP-1
金泊片
Gold sheet

金色亮片状，阻燃泊片材质，尺寸2*5CM，超薄，易上飘。
容量：1KG/包 40包/箱

Gold sheet, flame retardant plate material, size: 2*5CM, ultra-thin, easy to float.
Capacity: 1KG / package 40 bags / carton



CP-2
彩色亮片
Color Gold sheet

彩色亮片状，阻燃泊片材质，尺寸2*5CM，超薄，易上飘。
容量：1KG/包 40包/箱

Color golad sheet, flame retardant / non-flame retardant paper material, size :2 * 5CM, thin, easy to float.
Capacity: 1KG / package 40 bags / carton



CP-3
彩片纸
Color paper sheet

彩色片状，阻燃型/非阻燃纸片材质，尺寸2*5CM，轻薄，易上飘。
容量：1KG/包 40包/箱

Color paper sheet, flame retardant / non-flame retardant paper material, size :2 * 5CM, thin, easy to float.
Capacity: 1KG / package 40 bags / carton



CP-4
电子礼炮弹
Electric Confetti Cartridge

电子线牵引式，80CM长管状，内置各型阻燃纸片材质，需通过彩炮枪设备运用！内置纸片尺寸2*5CM，轻薄，易上飘。
容量：500G/支 25支/箱

Electronic wire traction type, 80CM long tubular, built-in flame retardant paper material, Used on color gun equipment! The built-in paper size is 2*5CM, which is light and easy to float.
Capacity: 500g / PC 25PC /carton